

HANHUITM 汉辉
——让光更完美



深圳市汉辉光电有限公司

Shenzhen Hanhui Photoelectricity Co.,Ltd

地址: 深圳市宝安区石岩街道石龙仔社区恒昌荣高科技科技园3栋3楼
ADD: Area A No.3 Building 3th Floor,Hengchang Rong Industrial
Park shiyan,shilong community,Baoan District,shenzhen,china
TEL:86-755-29232420 FAX:86-755-83723765
<http://www.szhanhui.com> <http://linsen4880.1688.com>



深圳市汉辉光电有限公司
Shenzhen Hanhui Photoelectricity Co.,Ltd

关于我们 —

深圳市汉辉光电有限公司是一家集研发，设计，开模，生产销售为一体的国家高新技术企业。以精湛的技术设计和自动化专业制造以及严格的生产管理体系，提供LED室内外照明，激光投影，车灯等光学类产品服务，公司建立完善的ISO9001质量管理体系，均通过ROHS规格要求。

汉辉光电在光学透镜研发设计领域是一家有自主知识产权的高新企业，在LED光学应用领域具有强大的开发和模具制造经验与能力。公司可以针对任何品牌的LED进行设计，开发出专案理想的透镜，也会针对世界各大品牌开发出自己的产品并获得一些专利。目前开发出匹配CREE PHILIPS SSC PROLINHT HELIO EDISON EVERLIGE LG等光源厂的单颗多颗连体等各尺寸规格专用的透镜。

汉辉光电一直以产品质量为根本，原材料均采用环保光学级PMMA或V2-PC户外专用的5VA-PC，并保证一次性使用，绝不添加和使用水口料。以优良的管理制度体系来保证产品质量。市场应用产品：路灯、天花灯、射灯、舞台灯、投光灯、洗墙灯、筒灯、手电、车载、投影显示、鞋盒灯、仓库灯.....

公司秉承：品质第一，追求卓越，科技创新，诚信经营的理念，期待与您携手共创辉煌。



About us

Shenzhen Hanhui Photoelectricity Co.,Ltd. is a National high-tech enterprises integrating r&d, design, mold opening and production sales. By the exquisite design and automation professional manufacturing technology and strict production management system, and provide the LED indoor and outdoor lighting, laser projection, lights and other optical products services, the company set up perfect ISO9001 quality management system, passed ROHS specifications.

Hanhui Photoelectricity In the field of optical lens development and design, there are high and new enterprises with independent intellectual property rights. In the field of LED optical applications, there are strong development and mold manufacturing experience and capability. The company can design and develop the ideal lens for the LED of any brand and develop its own product for the world's major brands and obtain some patents. At present, we have developed a special lens for each size specification, such as single multi-piece conjoined, etc., which match CREE PHILIPS SSC PROLINHT HELIO EDISON EVERLIGE LG.

Hanhui Photoelectricity The product quality is always based on the environmental protection optical level PMMA or v2-pc outdoor special 5va-pc, and guaranteed to be used once, never add and use the water. Good management system to ensure product quality. Market application products: Street lamps/Ceiling lamp/Shoot the light/The stage light/Project-light lamp/Wash the wall lamp/Canister light/A torch/On-board projection display/Shoe lights/Warehouse lights.

The company adheres to: quality first, the pursuit of excellence, scientific and technological innovation. the integrity management concept, looks forward to join hands with you to create brilliant.





一个品牌就是一份责任，一种信誉，一个保证
One brand means one responsibility, One credit and one assurance



认真是我们对客户的责任
Conscientiousness is our responsibility to our customers.

认真是我们对工作的态度
Conscientiousness is our attitude towards work.





认真是我们生存的方式
Conscientiousness is the way we live.


理念：我们本着共赢的态度，专业的技术，为客户打造匠心的产品
Philosophy: we are based on a win-win attitude, professional technology, to create a product for customers.

**工作我们是认真的，
服务我们是用心的**

We're serious about work,
The service is intentional.



户外壁灯
Outdoor wall lamp





基本信息/General Information


型号/Model No.	尺寸/Size (mm)	材料/Material	光源/Light Source	透过率/Transmittance	标准/Standard
HH-248	311.8×208.3×64.8	PC	3030/2835	90%	SSL Technical Requirements V4.3
HH-285	323×167.36×58	PC	3030/2835	90%	SSL Technical Requirements V4.3
	252×244	PC	3030/2835	90%	SSL Technical Requirements V4.3

配光曲线/Light Distribution

SSL Technical Requirements V4.3							
Model	VAC	Flux (lm)	Flux (lm) (0-90°)	P (W)	Eff (lm/W) (0-90°) Standard	Eff (lm/W) (0-90°) Standard	Zonal Lumen Requirements
Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires		300-5000			≥87.3	≥106.7	80-90° / 0-90° ≤13%
		5000-10000			≥92.15	≥111.55	
		≥10000			≥97	≥116.4	



	80-90° / 0-90°
HH-248	10.4%
HH-285	11.7%




基本信息/General Information

型号/Model No.	尺寸/Size (mm)	材料/Material	光源/Light Source	透过率/Transmittance	标准/Standard
HH-249	252.5×120×8.5	PC	3030/2835	90%	SSL Technical Requirements V4.3
HH-250	157.58×72.5×8.45	PC	3030/2835	90%	SSL Technical Requirements V4.3
HH-251	292×150×8.45	PC	3030/2835	90%	SSL Technical Requirements V4.3
HH-252	208.55×92.5×8.5	PC	3030/2835	90%	SSL Technical Requirements V4.3
HH-253	259.58×102.5×8.5	PC	3030/2835	90%	SSL Technical Requirements V4.3

配光曲线/Light Distribution



SSL Technical Requirements V4.3					
Primary Use Designation	Minimum Light Output (lm)	Zone/Spacing Criteria	ZLD/SC Nominal Requirement	ZLD/SC Tolerance	ZLD/SC Requirement with Tolerance
Outdoor Full-Cutoff Wall-Mounted Area Luminaires	300	0-90°	100%	-3%	≥97%
		80-90°	≤10%	+3%	≤13%





Zone	Lumens	%Lamp	%Fixt
0-20	914.71	17.90	17.90
0-30	1838.61	35.90	35.90
0-40	2863.32	55.90	55.90
0-60	4552.39	88.90	88.90
0-80	5111.49	99.90	99.90
0-90	5120.49	100.00	100.00
10-90	4868.52	95.10	95.10
20-40	1948.61	38.10	38.10
20-50	2907.72	56.80	56.80
40-70	2104.12	41.10	41.10
60-80	559.09	10.90	10.90
70-80	144.05	2.80	2.80
80-90	9.00	0.20	0.20
90-110	0.00	0.00	0.00
90-120	0.00	0.00	0.00
90-130	0.00	0.00	0.00
90-150	0.00	0.00	0.00
90-180	0.00	0.00	0.00
110-180	0.00	0.00	0.00
0-180	5120.49	100.00	100.00

Zone/Spacing Criteria	Test Result	Meet Demand
0-90°	100%	✓
80-90°	0.2%	✓



工矿灯-透镜
Mining lamp - lens.





型号/Model No.	HH-49-204×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	220×7.48
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	204
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-65A-150×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	208×11.7
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	150
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-50-50×1-90-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	160×8.5
光源/Light Source	3030/2835/5050
光源颗数/The Number of Light Source	50
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-66A-260×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	252.39×11.7
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	260
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-69-52×1-90-2835
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	110×9.5
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	52
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-84-156×1-60-2835
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	166×9.5
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	156
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-83-104×1-75-2835
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	140×9.5
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	104
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light






型号/Model No.	HH-129-208×1-60-2835
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	235×14
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	208
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light






型号/Model No.	HH-88-376×1-60-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	339×14
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	376
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-100-252×1-60-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	270×15.18
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	252
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-89-483×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	339×14
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	483
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-99-336×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	217.5×8.2
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	336
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-142-714×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	269×8.2
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	714
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-192-210×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	195.46×11.67
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	210
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light






型号/Model No.	HH-171-121×4-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	217.5×8.5
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	484
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-193-350×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	241.48×11.71
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	350
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-194-420×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	278×11.71
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	420
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-182-105×1-xx-3737
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	219.48×219.48×14
光源/Light Source	3737/5050
光源颗数/The Number of Light Source	105
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	球场灯/Court Lamp






型号/Model No.	HH-195-540×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	278×11.71
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	540
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-206-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	184×9.5
光源/Light Source	3030/2835/5050
光源颗数/The Number of Light Source	不限/Unlimited
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-207-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	226×11.5
光源/Light Source	3030/2835/5050
光源颗数/The Number of Light Source	不限/Unlimited
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light




型号/Model No.	HH-308-5-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	233.12×8.8
光源/Light Source	2835/3030
光源颗数/The Number of Light Source	不限/Unlimited
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-208-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	265×11.5
光源/Light Source	3030/2835/5050
光源颗数/The Number of Light Source	不限/Unlimited
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	工矿灯/High Bay Light




型号/Model No.	HH-310-7-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	293.12×8.8
光源/Light Source	2835/3030
光源颗数/The Number of Light Source	不限/Unlimited
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light




型号/Model No.	HH-322-75×4-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	233.1×9
光源/Light Source	2835/3030
光源颗数/The Number of Light Source	300
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





型号/Model No.	HH-323-154×4-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	293.1×9
光源/Light Source	2835/3030
光源颗数/The Number of Light Source	616
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	工矿灯/High Bay Light





球场灯路灯透镜
stadium light street lamp lens.





HANHUI™ 汉辉
让光更完美





型号/Model No.	HH-85-1×4-T2-S-3030
材料/Material	PC/PMMA
透过率/Transmittance	92%
尺寸/Size (mm)	23×16
光源/Light Source	3030
光源颗数/The Number of Light Source	4
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light





型号/Model No.	HH-105-56×2-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	230×150
光源/Light Source	3030
光源颗数/The Number of Light Source	112
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	路灯/Street Light





型号/Model No.	HH-115-8×1-xx-7070
材料/Material	PC/PMMA
透过率/Transmittance	92%
尺寸/Size (mm)	124×75
光源/Light Source	7070
光源颗数/The Number of Light Source	8
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light





型号/Model No.	HH-105-42×4-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	230×150
光源/Light Source	3030
光源颗数/The Number of Light Source	168
配光数量/The Number of Light Distribution	3
典型应用/Typical Application	路灯/Street Light





型号/Model No.	HH-64-96×1-60-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	235×144
光源/Light Source	3030
光源颗数/The Number of Light Source	96
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	投光灯/Flood Light






型号/Model No.	HH-146-12×4-T2-M-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	165×83
光源/Light Source	3030
光源颗数/The Number of Light Source	48
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light



型号/Model No.	HH-80-126×1-xx-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	241.35×170.35
光源/Light Source	3030
光源颗数/The Number of Light Source	126
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	投光灯/Flood Light





型号/Model No.	HH-120-80×1-60150-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	185×116
光源/Light Source	3030
光源颗数/The Number of Light Source	80
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	投光灯/Flood Light





HH-118-60150

型号/Model No.	HH-118-80×1-60150-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	295×80
光源/Light Source	3030
光源颗数/The Number of Light Source	80
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	投光灯/Flood Light





HH-19-70150

型号/Model No.	HH-19-28×1-70150-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	260×68
光源/Light Source	3030
光源颗数/The Number of Light Source	28
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light




HH-23-60°

型号/Model No.	HH-23-21×1-60-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	210×69.5
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	21
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	投光灯/Flood Light






HH-157-T3







型号/Model No.	HH-157-36×4-T3-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	276.3×95
光源/Light Source	3030
光源颗数/The Number of Light Source	144
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light





型号/Model No.	HH-166-24×1-T2-S-2835
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	178.51×102.51
光源/Light Source	3030/2835
光源颗数/The Number of Light Source	24
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light




型号/Model No.	HH-238-336×1-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	336
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	5
尺寸/Size (mm)	360×172	典型应用/Typical Application	投光灯/Flood Light





型号/Model No.	HH-168-18×4-T2-M-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	170×100.52
光源/Light Source	3030
光源颗数/The Number of Light Source	72
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light




型号/Model No.	HH-284-24×4-T2-M-3030
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	160×125.49
光源/Light Source	3030
光源颗数/The Number of Light Source	96
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	路灯/Street Light











型号/Model No.	HH-333-1-10-3737
材料/Material	PC/PMMA
透过率/Transmittance	92%
尺寸/Size (mm)	50×50×12.8
光源/Light Source	3737
光源颗数/The Number of Light Source	4
配光数量/The Number of Light Distribution	1
典型应用/Typical Application	投光灯/Flood Light




基本信息/General Information

型号/Model No.	HH-93-12×1-XX-3030	光源/Light Source	3030/2835
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	12
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	8
尺寸/Size (mm)	50×50	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light


配光曲线/Light Distribution






W: 14m H: 10m D: 40m Single row Lamp Flux: 14400lm							
	Lav (cd/ m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Ea
Count	1.14	0.52	0.86	12	0.57	12	0.466
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓





W: 16m H: 10m D: 40m Single row Lamp Flux: 17500lm							
	Lav (cd/ m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.20	0.59	0.83	9	0.64	13	0.505
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



W: 12m H: 10m D: 25m Single row Lamp Flux: 17500lm							
	Lav (cd/ m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Ea
Count	2.00	0.64	0.73	6	0.63	22	0.621
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



型号/Model No.	HH-332-24×1-xx-3030
材料/Material	PC/PMMA
透过率/Transmittance	92%
尺寸/Size (mm)	50×50
光源/Light Source	2835/3030
光源颗数/The Number of Light Source	24
配光数量/The Number of Light Distribution	2
典型应用/Typical Application	投光灯/Flood Light




基本信息/General Information

型号/Model No.	HH-109-4×1-XX-5050	光源/Light Source	5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	4
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	9
尺寸/Size (mm)	50×50	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light

基本信息/General Information

型号/Model No.	HH-116-4×4-XX-3030	光源/Light Source	3030/2835
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	16
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	12
尺寸/Size (mm)	50×50	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light


配光曲线/Light Distribution



HH-109-T2-M	W: 7.5m H: 10m D: 40m Single row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	1.48	0.59	0.73	12	0.78	19
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15
HH-109-T3-M	W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	1.05	0.50	0.79	13	0.65	16
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15



HH-109-T4-M	W: 21m H: 10m D: 30m Double row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	1.87	0.71	0.88	9	0.8	30
	Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15
HH-109-T3-S	W: 16m H: 10m D: 40m Single row Lamp Flux: 17280lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	1.18	0.45	0.87	10	0.63	13
	Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15

配光曲线/Light Distribution



HH-116-T2-M	W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	1.35	0.51	0.73	10	0.71	19
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15
HH-116-T3-M	W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	0.93	0.46	0.68	11	0.67	15
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15


HH-116-T2-M-B	W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	1.35	0.51	0.73	10	0.71	19
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15
HH-116-T3-M-B	W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm						
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)
	Count	0.93	0.46	0.68	11	0.67	15
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15



基本信息/General Information

型号/Model No.	HH-230-6×4-XX-3030	光源/Light Source	3030
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	24
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	2
尺寸/Size (mm)	59.6×49.6	典型应用/Typical Application	路灯/Street Light


配光曲线/Light Distribution





基本信息/General Information

型号/Model No.	HH-235-6×1-XX-5050	光源/Light Source	5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	6
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	3
尺寸/Size (mm)	49.6×49.6	典型应用/Typical Application	路灯/Street Light

配光曲线/Light Distribution






基本信息/General Information

型号/Model No.	HH-298-16×1-XX-3030	光源/Light Source	3030/2835
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	16
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	9
尺寸/Size (mm)	50×50	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light

配光曲线/Light Distribution




	W: 14m H: 10m D: 40m Single row Lamp Flux: 14400lm							
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
	Count	1.14	0.52	0.86	12	0.57	12	0.466
	Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
	Result	✓	✓	✓	✓	✓	✓	✓

	W: 12m H: 10m D: 25m Single row Lamp Flux: 17500lm							
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
	Count	1.96	0.67	0.79	8	0.67	20	0.680
	Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
	Result	✓	✓	✓	✓	✓	✓	✓

基本信息/General Information



型号/Model No.	HH-112-144×1-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	144
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	284.96×132.96	典型应用/Typical Application	路灯/Street Light、停车场灯/parking lot light

配光曲线/Light Distribution



	W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm							
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
	Count	0.88	0.43	0.75	12	0.64	14	0.448
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
	Result	✓	✓	✓	✓	✓	✓	✓


	W: 15m H: 10m D: 35m Double row Lamp Flux: 17500lm							
		Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
	Count	1.54	0.60	0.68	8	0.66	26	0.445
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
	Result	✓	✓	✓	✓	✓	✓	✓



基本信息/General Information

型号/Model No.	HH-127-72×1-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	72
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	250.75×74.75	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light


配光曲线/Light Distribution





基本信息/General Information

型号/Model No.	HH-150-64×2-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	128
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	280×90	典型应用/Typical Application	路灯/Street Light、投光灯/Flood Light

配光曲线/Light Distribution






基本信息/General Information

型号/Model No.	HH-130-105×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	420
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	5
尺寸/Size (mm)	352.5×230.4	典型应用/Typical Application	路灯/Street Light、投光灯/Flood Light


配光曲线/Light Distribution





基本信息/General Information

型号/Model No.	HH-131-70×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	280
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	5
尺寸/Size (mm)	283.3×181	典型应用/Typical Application	路灯/Street Light、投光灯/Flood Light

配光曲线/Light Distribution







基本信息/General Information

型号/Model No.	HH-132-35×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	140
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	5
尺寸/Size (mm)	218×141.25	典型应用/Typical Application	路灯/Street Light、投光灯/Flood Light

配光曲线/Light Distribution




HH-132-90°




HH-132-T2

W: 7.5m H: 10m D: 40m Single row Lamp Flux: 17500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.31	0.47	0.79	12	0.69	19	0.405
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




HH-132-T5



HH-132-T3

W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.91	0.40	0.76	14	0.63	14	0.409
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




HH-132-T4

W: 14m H: 12m D: 42m Double row Lamp Flux: 26000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.99	0.41	0.77	12	0.67	16	0.455
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓

基本信息/General Information


型号/Model No.	HH-146-18×4-XX-3030	光源/Light Source	3030/2835
材料/Material	PC	光源颗数/The Number of Light Source	72
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	148.8×86.5	典型应用/Typical Application	路灯/Street Light

配光曲线/Light Distribution




HH-146-T2-M

W: 7.5m H: 10m D: 40m Single row Lamp Flux: 15000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.92	0.46	0.82	15	0.77	12	0.468
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




HH-146-T3-S

W: 11.25m H: 10m D: 30m Single row Lamp Flux: 15000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.79	0.51	0.82	7	0.62	15	0.544
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓





HH-146-T3-S

W: 11.25m H: 10m D: 40m Single row Lamp Flux: 20000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.79	0.40	0.65	10	0.70	13	0.469
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



HH-146-T3-M


W: 7.5m H: 10m D: 40m Single row Lamp Flux: 15000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.96	0.44	0.77	15	0.77	12	0.459
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




基本信息/General Information

型号/Model No.	HH-181-36×4-XX-3030	光源/Light Source	3030/2835
材料/Material	PC	光源颗数/The Number of Light Source	144
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	253×120	典型应用/Typical Application	路灯/Street Light、停车场灯/Parking lot Light

配光曲线/Light Distribution




HH-181-T5




HH-181-T2

W: 7.5m H: 10m D: 35m Single row Lamp Flux: 15000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.09	0.58	0.83	9	0.75	16	0.561
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



HH-181-T3

W: 11.25m H: 10m D: 40m Single row Lamp Flux: 15000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.85	0.44	0.79	10	0.65	13	0.477
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




HH-181-T4

W: 14m H: 10m D: 35m Double row Lamp Flux: 25000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.02	0.42	0.81	12	0.70	17	0.509
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓


基本信息/General Information

型号/Model No.	HH-212-58×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	232
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	6
尺寸/Size (mm)	279×150	典型应用/Typical Application	路灯/Street Light


配光曲线/Light Distribution




HH-212-90120



HH-212-T3-S




HH-212-T5-M




HH-212-T2-M

W: 7.5m H: 10m D: 35m Single row Lamp Flux: 17500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.43	0.55	0.64	10	0.71	20	0.580
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




HH-212-T3-M

W: 11.25m H: 10m D: 40m Single row Lamp Flux: 17500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.93	0.42	0.67	11	0.69	15	0.434
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓





HH-212-T3-S

W: 10.5m H: 10m D: 30m Single row Lamp Flux: 17500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.15	0.47	0.68	10	0.60	19	0.714
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



HH-212-T4-M


W: 14m H: 12m D: 42m Single row Lamp Flux: 25000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	0.88	0.45	0.87	14	0.68	13	0.488
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



基本信息/General Information

型号/Model No.	HH-213-22×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	88
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	308.1×45	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light


配光曲线/Light Distribution





基本信息/General Information

型号/Model No.	HH-214-20×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	80
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	210×104	典型应用/Typical Application	路灯/Street Light、停车场灯/Parking Lot Light

配光曲线/Light Distribution







基本信息/General Information

型号/Model No.	HH-215-32×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	128
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	270×104	典型应用/Typical Application	路灯/Street Light、停车场灯/Parking Lot Light

配光曲线/Light Distribution




HH-215-T5-S




HH-215-T2-M

W: 16m H: 8m D: 30m Double row Lamp Flux: 13000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.68	0.73	0.78	10	0.84	27	0.455
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



HH-215-T3-M

W: 22m H: 10m D: 35m Double row Lamp Flux: 19500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.44	0.69	0.86	10	0.85	29	0.520
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓




HH-215-T4-M

W: 29m H: 12m D: 40m Double row Lamp Flux: 26000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.19	0.69	0.86	9	0.89	20	0.546
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓


基本信息/General Information

型号/Model No.	HH-216-42×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	168
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	290×126	典型应用/Typical Application	路灯/Street Light、停车场灯/Parking Lot Light

配光曲线/Light Distribution




HH-216-T5-S




HH-216-T2-M

W: 16m H: 8m D: 30m Double row Lamp Flux: 13000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.68	0.73	0.78	10	0.84	27	0.455
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓





HH-216-T3-M

W: 22m H: 10m D: 35m Double row Lamp Flux: 19500lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.44	0.69	0.86	10	0.85	29	0.520
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



HH-216-T4-M



W: 29m H: 12m D: 40m Double row Lamp Flux: 26000lm							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.19	0.69	0.86	9	0.89	20	0.546
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓





基本信息/General Information

型号/Model No.	HH-217-56×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	224
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	4
尺寸/Size (mm)	345×130	典型应用/Typical Application	路灯/Street Light、停车场灯/Parking Lot Light


配光曲线/Light Distribution



W: 16m H: 8m D: 30m Double row Lamp Flux: 13000lm							
	L_{av} (cd/m ²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.68	0.73	0.78	10	0.84	27	0.455
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



W: 22m H: 10m D: 35m Double row Lamp Flux: 19500lm							
	Lav (cd/m ²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.44	0.69	0.86	10	0.85	29	0.520
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓






W: 29m H: 12m D: 40m Double row Lamp Flux: 26000lm							
	Lav (cd/m ²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.19	0.69	0.86	9	0.89	20	0.546
Request	≥1.00	≥0.4	≥0.7	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓



基本信息/General Information

型号/Model No.	HH-256-56×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	224
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	3
尺寸/Size (mm)	240×165	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light

配光曲线/Light Distribution





W: 7.5m H: 10m D: 35m Single row Lamp Flux: 20000							
	Lav (cd/m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.03	0.52	0.76	9	0.68	18	0.550
Request	≥ 0.75	≥ 0.4	≥ 0.6	≤ 15	≥ 0.5	10/15	≥ 0.35
Result	✓	✓	✓	✓	✓	✓	✓




基本信息/General Information

型号/Model No.	HH-257-120×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	480
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	3
尺寸/Size (mm)	290×290	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light

配光曲线/Light Distribution








 <div>HH-257-T3-S</div>	W: 7.5m H: 10m D: 35m Single row Lamp Flux: 20000							
		Lav (cd/㎡)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
	Count	1.03	0.52	0.76	9	0.68	18	0.550
	Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
	Result	✓	✓	✓	✓	✓	✓	✓

基本信息/General Information

型号/Model No.	HH-242-64×1-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	64
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	5
尺寸/Size (mm)	236×70	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light

配光曲线/Light Distribution






HH-242-T3-M

W: 11.25m H: 10m D: 40m Single row Lamp Flux: 20000

	Lav (cd/ m²)	U0	UL	TI (%)	SR	Eav (lx)	Emin/Eav
Count	1.05	0.44	0.79	13	0.65	15	0.511
Request	≥0.75	≥0.4	≥0.6	≤15	≥0.5	10/15	≥0.35
Result	✓	✓	✓	✓	✓	✓	✓











Linear lamp




基本信息/General Information




型号/Model No.	HH-209-50×4-XX-3030	光源/Light Source	3030
材料/Material	PC	光源颗数/The Number of Light Source	200
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	7
尺寸/Size (mm)	285×133	典型应用/Typical Application	投光灯/Flood Light、路灯/Street Light

配光曲线/Light Distribution








型号/Model No.	HH-43-33×1-xx-5630
材料/Material	PC
透过率/Transmittance	92%
尺寸/Size (mm)	290.1×58.8
光源/Light Source	5630/3030
光源颗数/The Number of Light Source	33
配光数量/The Number of Light Distribution	4
典型应用/Typical Application	线型灯/Linear Light





型号/Model No.	HH-110-XX-2835	光源/Light Source	3030/2835
材料/Material	PMMA	光源颗数/The Number of Light Source	不限/Unlimited
透过率/Transmittance	92%	配光数量/The Number of Light Distribution	5
尺寸/Size (mm)	299×70	典型应用/Typical Application	线型灯/Linear Light




亮化透镜
Lighting lens




型号/Model No.	HH-36-FC-5050	光源/Light Source	5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	120°
尺寸/Size (mm)	7.5×7.5	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-186-15-3090-3030	光源/Light Source	3030
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	30×90°
尺寸/Size (mm)	14.07×14.92	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-32-15-30Z-5050	光源/Light Source	5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	30° /45° /60° /20×50°
尺寸/Size (mm)	Ø14.5	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-35-15-15F-XP-6B	光源/Light Source	3535/3030/2835
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	15° /25° /45° /10×60° /25×45° /40×60°
尺寸/Size (mm)	14.55×15.93	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-53-15-30Z-XP	光源/Light Source	3030/2835/3535
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	15° /30° /45° /60° /10×60° /25×60°
尺寸/Size (mm)	Ø15	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-09-21.5-10G-XP	光源/Light Source	3030/3535
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	10° /20° /35° /10×60° /30×60°
尺寸/Size (mm)	Ø21.5	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-03-1215G-XP	光源/Light Source	3030/3535
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	10° /15° /30° /45° /60° /10×60° /30×60°
尺寸/Size (mm)	Φ11.8	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-57-21.8-30G	光源/Light Source	仿流明
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	15° /30° /45° /60° /15×50° /30×60°
尺寸/Size (mm)	Φ21.8	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-P15-10G-XP	光源/Light Source	3535/3030
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	10° /15° /30° /45° /60° /10×60° /15×50° /30×60°
尺寸/Size (mm)	Φ15	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-HW17-20H	光源/Light Source	仿流明
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	20° /30° /45° /60° /90°
尺寸/Size (mm)	Φ18.96	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-01-2008G-XP	光源/Light Source	3030/3535
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	8° /15° /30° /45° /60° /85° /10×60° /30×60°
尺寸/Size (mm)	Φ20	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-HW20-20H	光源/Light Source	仿流明
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	20° /30° /45° /60° /90°
尺寸/Size (mm)	Φ20	典型应用/Typical Application	亮化/Brighten



型号/Model No.	HH-20-15-TWH	光源/Light Source	仿流明
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle (°)	8/10/15/25/30/45/60/90/120/15×60/25×60
尺寸/Size (mm)	Φ20	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-P17-20G-XML	光源/Light Source	XML 5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	20° /30° /45° /60° /70°
尺寸/Size (mm)	Φ17	典型应用/Typical Application	亮化/Brighten




型号/Model No.	HH-P20-15G-XML	光源/Light Source	XML 5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	15° /30° /45° /60°
尺寸/Size (mm)	Φ19.7	典型应用/Typical Application	亮化/Brighten

室内照明 Indoor lighting







型号/Model No.	HH-JC46-23-30HM	光源/Light Source	COB
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	30°
尺寸/Size (mm)	Φ46.18	典型应用/Typical Application	室内照明/Indoor Lighting




型号/Model No.	HH-P03B-2515G-XP	光源/Light Source	3535/3030
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	3
透过率/Transmittance	93%	配光角度/Beam Angle	15° /30° /45° /60°
尺寸/Size (mm)	Φ25	典型应用/Typical Application	室内照明/Indoor Lighting




型号/Model No.	HH-13-40-13-25	光源/Light Source	COB
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	25° /38°
尺寸/Size (mm)	Φ39.5	典型应用/Typical Application	室内照明/Indoor Lighting



型号/Model No.	HH-P35MM	光源/Light Source	3535/3030
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	3/4/5/7
透过率/Transmittance	93%	配光角度/Beam Angle	15° /25° /30° /38° /45° /60°
尺寸/Size (mm)	Φ35	典型应用/Typical Application	室内照明/Indoor Lighting



型号/Model No.	HH-38DT	光源/Light Source	3535/3030/5050
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	1
透过率/Transmittance	93%	配光角度/Beam Angle	5° ~60°
尺寸/Size (mm)	Φ8.5/12.5/16/19/23/27.7/29/35.8/38/44.8/60	典型应用/Typical Application	室内照明/Indoor Lighting



型号/Model No.	HH-P67MM	光源/Light Source	3535
材料/Material	PC/PMMA	光源颗数/The Number of Light Source	6/7/9/12/15/18/24/30/36
透过率/Transmittance	93%	配光角度/Beam Angle	15° /25° /30° /38° /45° /60°
尺寸/Size (mm)	Φ67	典型应用/Typical Application	室内照明/Indoor Lighting